

کتالـوج المنتجــات Product Catalog



Products

LED GU10 - MR16	3
LED Bulb Stick	4
LED Bulb Ball	5
LED - Wall Lamp	6
LED - Wall Light	7
LED - Cylinder Light	12
Panel Down Light-R	13
Panel Down Light	18
LED - 60x60 / 60 W	19
LED - 60x60 / 96 W	23
COB Down Light-R	27
Surface Panel Light-R	34
Surface Panel Light-S	39
Strip Light - 2 Lines	40
Strip Light - Waterproof	42
Strip Light - COB	44
Track Light - COB	46
Magnetic Track Light - COB	48
Magnetic Track Light - Laser	64
Magnetic Track Light - Spotlight	73



• LED GU10 - MR16



© ساعات التشغيل 30,000 h

کا 3000K, 4000K, 6500K

نوع الشريحة SMD

1 (اوية الانتشار 38°

Code	Power	Voltage	Size	IP	Lumin / W
GU10	7W	110 / 220	50 x 54	20	-
MR16	7W	110 / 220	50 x 52	20	-







LED Bulb Stick



© ساعات التشغيل 30,000 h


کا 3000K, 4000K, 6500K

نوع الشريحة SMD

زاوية الانتشار 🔼	38°
------------------	-----

Code	Power	Voltage	Size	IP	Lumin / W
Stick	9W	110 / 220	50 x 54	20	-
Stick	12W	110 / 220	50 x 52	20	-







LED Bulb Ball






کا 3000K, 4000K, 6500K

نوع الشريحة SMD

زاوية الانتشار 🔼	175°
------------------	------

Code	Power	Voltage	Size	IP	Lumin / W
Ball	50W	110 / 220	50 x 54	20	-







LED - Wall Lamp





کا الون الون 3000K, 4000K, 6500K


> 0.9معامل الطاقة

نوع الشريحة SMD

120° زاوية الانتشار

Code	Power	Voltage	Size	IP	Lumin / W
FL-WH22W	22W	110 / 220	120 x 70 x 265 mm	66	1672 L
FL- WWL22W	22W	110 / 220	140 x 70 x 265 mm	66	1672 L






About This Item


- Lash Waterproof dustproof outdoor wall LED wall light outdoor fence trails ga dens waterproof high light quality can not put large setting
- Color Light: white makes these outdoor lights perfect for lighting walls, posts, and botanicals. High Quality LED Light Chip.
- Widely Used Indoor, Outdoor, Landscape
 120 degree beam angle, easy home fence
 decoration, great decoration for indoor
 surfaces, fences, steps, corridor, walls and
 trees.

- **Mural** Suitable for outdoor fence composed of quality white light and white frame
- Shape Designed with stylish, fashionable and simple shape which is made of high quality plastic. Not Easy Color Fading. LED lamp saves electricity









2000K, 4000K, 6500K درجة اللون

\$	معامل الطاقة	> 0.9
----	--------------	-------

†

نوع الشريحة SMD

T	الانتشار	زاوية	120	0
----------	----------	-------	-----	---

Code	Power	Voltage	Size	IP	Lumin / W
FL-WL- 8WW	8W	110 / 220	220 x 70 mm	66	640 L
FL-WL- 6WW	6W	110 / 220	220 x 70 mm	66	640 L
FL-WL- 4WW	4W	110 / 220	65 x 50 mm	66	400 L
FL-WL- 8WW	8W	110 / 220	220 x 70 mm	66	640 L













About This Item

Contains eight lenses


This modern outdoor wall light features four interlaced LED beams (top and bottom) with focusing lenses for brighter and farther illumination—ideal for enhancing your home's exterior, porch, or garden. It's easy to install

with included screws and stickers, making it suitable for stairs, decks, and fences. Designed for durability, the light is IP66 water-proof and resistant to rain, snow, and harsh weather conditions, ensuring reliable performance year-round.










Description; LED Outdoor Wall Lamp

Main material: Aluminum+Engineering plastics

 $\begin{array}{l} \textbf{Specification} \\ \textbf{Energy saving, up to 85} \% \text{ energy saving} \\ \textbf{comparing to standard halogen and incandescent} \end{array}$

High quality light, high color rending, less heat, no UV or IR radiation
Build-in LED Driver
IP65


- Applications
 . Park
 . Square
 . Tourist attraction
 . Corridor








LUMINOUS INTENSITY DISTRIBUTION DIAGRAM




Illuminance at a Distance




illumination when the luminaire is at different distance.




LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



Illuminance at a Distance









LED - Cylinder Light





کرجة اللون الله 3000K, 4000K, 6500K

نوع الشريحة SMD

120 زاوية الانتشار	0
----------------------	---

Code	Power	Voltage	Size	IP	Lumin / W
FL-WL- 16WH	16W	110 / 220	110 x 50 mm	66	1280 L
FL-WL- 16WW	16W	110 / 220	110 x 50 mm	66	1280 L





About This Item

- Waterproof and dustproof outdoor wall lighting, LED outdoor wall lights, outdoor fence paths, gardens, waterproof, high light quality, large settings cannot be placed.
- Color Light: White and warm make these outdoor lights ideal for illuminating walls, columns and ceilings. High quality LED light chip,
- Widely used for indoor, outdoor and land-

scape 120 degree beam angle, easy

- home fence decoration, great decoration for indoor decks, fences, steps, driveway, walls and trees.
- Mural Suitable for outdoor fence composed of high-quality white or warm light and white or black body
- Style Design Stylish, modern and simple design made of high quality metal. The color is not easy to fade. LED lamp saves electricity





© ساعات التشغيل 30,000 h


کا 3000K, 4000K, 6500K


> 0.9 معامل الطاقة

نوع الشريحة SMD نوع الشريحة

ألومنيوم مادة التصنيع


Code	Power	Voltage	Size	IP	Lumin / W
FLPR.5	5W	110 / 220	3 inch	20	400 L
FLPR.7	7W	110 / 220	4 inch	20	560 L
FLPR.12	12W	110 / 220	5 inch	20	960 L
FLPR.15	15W	110 / 220	6 inch	20	1200 L
FLPR.20	20W	110 / 220	8 inch	20	1600 L






















LUMINOUS INTENSITY DISTRIBUTION DIAGRAM




AVERAGE BEAM ANGLE (50%):115.1 DEG

Illuminance at a Distance






LUMINOUS INTENSITY DISTRIBUTION DIAGRAM




AVERAGE BEAM ANGLE (50%):108.6 DEG

Illuminance at a Distance











© ساعات التشغيل 30,000 h


کرجة اللون الله 3000K, 4000K, 6500K


> 0.9معامل الطاقة


نوع الشريحة SMD

° 120 زاوية الانتشار 120 °

Code	Power Voltage		Size	IP	Lumin / W
PS.7	7W	110 / 220	4 inch	20	560 L
PS.15	15W	110 / 220	6 inch	20	1200 L
PS.20	20W	110 / 220	8 inch	20	1600 L



















ا درجة اللون 3000K, 4000K, 6500K





Code	Power	Voltage	Size	IP	Lumin / W
FL-PN60W	60W	110 / 220	595 x 595 mm	66	4800 L




About This Item

- · Contains four powerful lighting paths
- Metal body
- Unique design that adds beauty to your living space
- · Made of aluminum, high quality
- Long life span
- · Does not emit heat
- Low electricity consumption
- Soft, flicker-free lighting
- Easy to install recessed ceiling lighting
- Suitable for lighting homes, offices and schools







Description: LED PANEL LIGHT

Main material:


luminium+lron+Engineering plastics

Specification

Energy saving, up to 85% energy saving comparing to standard halogen and incandescent lampsHigh quality light, high color rending, less heat, no UV or IR radiation LED driver is included IP20

Applications


- . Shoping mall
- . Office buildings
- . Exhibition hall








LUMINOUS INTENSITY DISTRIBUTION DIAGRAM




AVERAGE BEAM ANGLE (50%):113.4 DEG

Illuminance at a Distance




















Code	Power	Voltage	Size	IP	Lumin / W
FL-PN96W	96W	110 / 220	595 x 595 mm	20	7296 L






About This Item

- · Contains four powerful lighting paths
- Metal body
- Unique design that adds beauty to your living space
- · Made of aluminum, high quality
- Long life span
- · Does not emit heat
- Low electricity consumption
- Soft, flicker-free lighting
- Easy to install recessed ceiling lighting
- Suitable for lighting homes, offices and schools











LUMINOUS INTENSITY DISTRIBUTION DIAGRAM




AVERAGE BEAM ANGLE (50%):113.4 DEG

Illuminance at a Distance











CRI - درجة الوضوح > **80**



30,000 h ساعات التشغيل



2000K, 4000K, 6500K درجة اللون



> 0.9



نوع الشريحة

SMD



ألومنيوم مادة التصنيع

Code	Power	Voltage	Size	IP	Lumin / W	Beam Angle
FLTD7W	7W	110 / 220	70 mm	20	532 L	45°
FLTD11W	11W	110 / 220	100 mm	20	1100 L	45°
FLTD16W	16W	110 / 220	140 mm	20	1440 L	60°
FLTD20W	20W	110 / 220	150 mm	20	1760 L	60°
FLTD30W	30W	110 / 220	200 mm	20	2280 L	90°
FLTD60W	60W	110 / 220	200 mm	20	4560 L	90°










About This Item

The Downlight Full Light is a ceiling-mounted indoor fixture with even light distribution. Made of aluminum, glass, and a white frame, it's modern, lightweight, and corrosion-resistant. Easy to install, it suits various interior styles and offers high-quality decorative lighting.









Description:

LED CL103COB Series Down Light

Main material:

Die-cast aluminum+ glass cover

Specification

Energy saving, upto 85% energy saving comparing to standard halogen and incadescent lamps Long life, up to 30,000 hours High quality light, high color rending, rending, less heat, no UV or IR radiation Build-in LED driver


Applications

- . Shopping mall
- . Office buildings
- , Exhibition hall
- , Public lighting places






LUMINOUS INTENSITY DISTRIBUTION DIAGRAM




AVERAGE BEAM ANGLE (50%):33.3 DEG

Illuminance at a Distance






LUMINOUS INTENSITY DISTRIBUTION DIAGRAM




AVERAGE BEAM ANGLE (50%):37.5 DEG

Illuminance at a Distance






LUMINOUS INTENSITY DISTRIBUTION DIAGRAM




AVERAGE BEAM ANGLE (50%):99.4 DEG

Illuminance at a Distance






LUMINOUS INTENSITY DISTRIBUTION DIAGRAM




AVERAGE BEAM ANGLE (50%):53.8 DEG

Illuminance at a Distance









Surface Panel Light-R







3000K, 4000K, 6500K


\$	معامل الطاقة	> 0.9
----	--------------	-------


نوع الشريحة SMD


₽	مادة التصنيع	ألومنيوم
----------	--------------	----------

Code	Power	Voltage	Size	IP	Lumin / W
FLSP.6	6W	110 / 220	100 mm	20	480 L
FLSP.12	12W	110 / 220	150 mm	20	960 L
FLSP.20	20W	110 / 220	200 mm	20	1600 L
FLSP.30	30W	110 / 220	300 mm	20	2400 L














Surface Panel Light-R






Aluminium+Engineering plastics

Specification

Energy saving, up to 85% energy saving comparing to standard halogen and incandescent lampsHigh quality light, high colorrending, less heat, no UV or IR radiation LED driver is included IP20

Applications

- . Shoping mall
- . Office buildings
- . Exhibition hall









Surface Panel Light-R

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



AVERAGE BEAM ANGLE (50%):113.3 DEG


Illuminance at a Distance






Surface Panel Light-R

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM




AVERAGE BEAM ANGLE (50%):113.4 DEG

Illuminance at a Distance






Surface Panel Light-R





Surface Panel Light-S





کرجة اللون الله 3000K, 4000K, 6500K


♦ معامل الطاقة > 0.9


نوع الشريحة SMD


° 120 زاوية الانتشار 🗅


Code	Power	Voltage	Size	IP	Lumin / W
SPS.6	6W	110 / 220	4 inch	20	480 L
SPS.12	12W	110 / 220	6 inch	20	560 L
SPS.20	20W	110 / 220	8 inch	20	1600 L
SPS.30	30W	110 / 220	10 inch	20	2400 L















Strip Light - 2 Lines



© ساعات التشغيل 30,000 h

کرجة اللون الله 3000K, 4000K, 6500K

2835 نوع الشريحة

2 عدد الليد / متر الله / متر

Code	Power	Voltage	Size	IP	Lumin / W
FL.3000	15W	220 - 240	20 cm	65	1400 L
FL.4000	15W	220 - 240	20 cm	65	1400 L
FL.6500	15W	220 - 240	20 cm	65	1400 L










Strip Light - 2 Lines



Installation step

Before finish the installation, do not connect the power

 According to practical demand, Fix the strip with clip and screws in needed place (The strip is good flexibility for any shape)



2.Use shape pin to connect the strip and power supply cord .Then glue the interface



3. Cut the strip according to your requirement (each 1 meter can be cut for 220V strip .)



4. Close the strip with end cap and glue with the designative glue for safety and waterproof





Strip Light - Waterproof



© ساعات التشفيل 30,000 h

کرجة اللون 3000K, 4000K, 6500K

> 0.9 معامل الطاقة

نوع الشريحة 2835

20 L عدد الليد / متر

Code	Power	Voltage	Size	IP	Lumin / W
FL.3000	10W	220 - 240	20 cm	65	1400 L
FL.4000	10W	220 - 240	20 cm	65	1400 L
FL.6500	10W	220 - 240	20 cm	65	1400 L










Strip Light - Waterproof





Description: LED ROPE LIGHT

Main material: aluminum+PC cover engineering plastic High quality aluminum spherical reflector for soft and comfortable light.

Specification:
Energy saving,up to 85% energy saving comparing to standard halogen and incandescent lamps
Long life,up to 50,000 hours
High quality light,high color rending,less heat, no UV or IR radiation

Applications Shopping mall Office buildings, exhibition hall and so on public lighting places , Domestic



Strip Light - COB



© ساعات التشغيل 30,000 h

کا 3000K, 4000K, 6500K

🗓 2835 نوع الشريحة

الطاقة > 0.	9
-------------	---

Code	Power	Voltage	Size	IP	Lumin / W
FL.3000	-	220 - 240	50 cm	20	-
FL.4000	10W	220 - 240	50 cm	20	-
FL.6500	10W	220 - 240	50 cm	20	-











Strip Light - COB



How to Use COB LED Strip Light







Track Light - COB



© ساعات التشفيل 30,000 h

کا 3000K, 4000K, 6500K

© نوع الشريحة COB

داخلي انوعه 🖪

Code	Power	Voltage	Size	IP	Lumin / W
FL.TD30WH	30W	110 / 240	170 x 95 x 170	20	2400 L
FL.TD30WW	30W	110 / 240	170 x 95 x 170	20	2400 L












Track Light - COB

Aluminum body

170mm







APPLICATION







Description: LED Track Light

Main material:


Engineering plastic high quality aluminum.


Specification:

Energy saving, up to 85% energy saving comparing to standard halogen and in candescent lamps Long life, up to 30,000 hours High quality light, High color rending, less heat, no UV or IR radiation Build-in LED driver.

Applications

- •Shopping mall •Office buildings
- •Exhibition hall

















Code	Power	Voltage	Size	IP	Lumin / W
FL.12W/40K	12W	110 / 240	215 x 22 x 25 mm	20	876 L
FL.18W/40K	18W	110 / 240	322 x 22 x 25 mm	20	1314 L
FL.24W/40K	24W	110 / 240	600 x 22 x 44 mm	20	1752 L
FL.30W/40K	30W	110 / 240	900 x 22 x 44 mm	20	2190 L






About This Item

A premium product from Full Light, this magnetic laser lamp features anti-glare laser lenses, a durable aluminum body, and heat- and dust-resistant paint. Available in 3000K and 4000K with power options from 12W to 30W, it's easy to install on a 48V magnetic track. Its built-in transducer ensures lighting stability and longer lifespan. With a sleek black frame, 5-year warranty, and energy-saving performance, it's ideal for adding elegance to offices, homes, and shops.









Description:

LED Magnetic Track System

Main material:


Aluminum shell, engineering plastic

Specification:

Energy saving, up to 85% energy saving comparing to standard halogen and incandescent lamps
High quality light, high color rending, less heat, no UV or IR radiation
Build-in LED Driver

Applications


- ,Office
- ,Meeting room
- ,Sitting room








LUMINOUS INTENSITY DISTRIBUTION DIAGRAM




AVERAGE BEAM ANGLE (50%):20.7 DEG






LUMINOUS INTENSITY DISTRIBUTION DIAGRAM




AVERAGE BEAM ANGLE (50%):53.6 DEG






LUMINOUS INTENSITY DISTRIBUTION DIAGRAM




AVERAGE BEAM ANGLE (50%):23.5 DEG






LUMINOUS INTENSITY DISTRIBUTION DIAGRAM




AVERAGE BEAM ANGLE (50%):56.7 DEG






LUMINOUS INTENSITY DISTRIBUTION DIAGRAM




AVERAGE BEAM ANGLE (50%):24.2 DEG






LUMINOUS INTENSITY DISTRIBUTION DIAGRAM




AVERAGE BEAM ANGLE (50%):54.7 DEG






LUMINOUS INTENSITY DISTRIBUTION DIAGRAM




AVERAGE BEAM ANGLE (50%):21.6 DEG






LUMINOUS INTENSITY DISTRIBUTION DIAGRAM




AVERAGE BEAM ANGLE (50%):56.5 DEG






LUMINOUS INTENSITY DISTRIBUTION DIAGRAM




AVERAGE BEAM ANGLE (50%):21.5 DEG






LUMINOUS INTENSITY DISTRIBUTION DIAGRAM




AVERAGE BEAM ANGLE (50%):63.9 DEG






LUMINOUS INTENSITY DISTRIBUTION DIAGRAM




AVERAGE BEAM ANGLE (50%):20.4 DEG






LUMINOUS INTENSITY DISTRIBUTION DIAGRAM




AVERAGE BEAM ANGLE (50%):63.2 DEG







LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



AVERAGE BEAM ANGLE (50%):63.2 DEG













کا 3000K, 4000K, 6500K



© COB نوع الشريحة

国	نوعه	داخلی
		• •

Code	Power	Voltage	Size	IP	Lumin / W
FL.12W/40K	12W	110 / 240	215 x 22 x 25 mm	20	876 L
FL.18W/40K	18W	110 / 240	322 x 22 x 25 mm	20	1314 L
FL.24W/40K	24W	110 / 240	600 x 22 x 44 mm	20	1752 L
FL.30W/40K	30W	110 / 240	900 x 22 x 44 mm	20	2190 L






About This Item

This premium magnetic laser light from Full Light features powerful anti-glare lenses, a durable aluminum body, and dust- and heat-resistant paint. Available in 12W, 18W, 24W, and 30W, it's easy to install and move along a 48V magnetic track. A built-in transducer ensures stable lighting and extended lifespan. With a sleek black frame, 5-year warranty, and energy-efficient performance, it adds elegance and sophistication to offices, homes, and shops.
































Item Code	P(W)	Using TracK	Color	Input	Output Current	Dimer A	nsions B	in mm C	kg
fl-power-48V-100W	100	fl-out-20	BlacK/White	AC220-240V 50/60Hz Max:0.5A	DC48V = 2A Max	240	22	43	0.26
fl-power-48V-200W	200	fl-out-20	BlacK/White	AC220-240V 50/60Hz Max:1A	DC48V = 4A Max	310	22	43	0.36
fl-power-48V-100W	100	fl-in-30	BlacK/White	AC220-240V 50/60Hz Max:0.5A	DC48V == 2A Max	153	35	68	0.47
fl-power-48V-200W	200	fl-in-30	BlacK/White	AC220-240V 50/60Hz Max:1A	DC48V = 4A Max	182	35	68	0.56







Picture	Item Code	Material	Size in mm	Hole Size (mm)	kg
	f l-out-20	Aluminum	50*26*1500 50*26*3000		1.34 2.68
	fl-out-30	Aluminum	75*38*1500 75*38*3000		1.86 3.72
	fl-in-20	Aluminum	50*41*1500 50*41*3000	30*1500 30*3000	1.40 2.80
	fl-in-30	Aluminum	75*54*1500 75*54*3000	40*1500 40*3000	1.90 3.80
	fl-L-20	Aluminum	50*65*65		0.06
	fl-L-30	Aluminum	75*67*67		0.09




Picture	Item Code	Material	Size in mm	kg
1	fl-L-100-200-power	PC	148*15* 17	0.05
	fl-20-connect	PC	148*15* 17	0.02
	fl-L-CONNECT	PC	450*15*17	0.05
	fl-S-ACS	Iron	70*54* 23	0.05
	fl-B-ACS	Iron	100*54*23	0.06
	fl-Wire-1M fl-Wire-2M	Iron	1M 2M	0.07


























ك معامل الطاقة ♦ 3000K, 4000K, 6500K درجة اللون > 0.9

داخلي انوعه 🗗 COB نوع الشريحة 🤠

Code	Power	Voltage	Size	IP	Lumin / W
FL.10W/BK	12W	110 / 240	48 x 135 mm	20	2400 L
FL.20W/BK	24W	110 / 240	65 x 300 mm	20	2400 L





About This Item

This elegant product from Full Light features a durable aluminum body with dust- and heat-resistant paint. Available in 12W and 24W, it's easily installed and moved on a 48V magnetic track. Made from two metals, it offers enhanced performance and longevity. With a 5-year warranty, a sleek black frame, and energy-efficient operation, it adds a touch of sophistication to offices, homes, and shops.









Description:

LED Magnetic Track System

Main material:

Aluminum shell

Specification:

Energy saving, up to 85% energy saving comparing to standard halogen and incandescent lamps High quality light, high color rending, less heat, no UV or IR radiation


Build-in LED Driver

Applications

,Office

,Meeting room


,Sitting room








LUMINOUS INTENSITY DISTRIBUTION DIAGRAM




AVERAGE BEAM ANGLE (50%):23.2 DEG

Illuminance at a Distance






LUMINOUS INTENSITY DISTRIBUTION DIAGRAM




AVERAGE BEAM ANGLE (50%):34.1 DEG

Illuminance at a Distance






LUMINOUS INTENSITY DISTRIBUTION DIAGRAM




AVERAGE BEAM ANGLE (50%):34.5 DEG

Illuminance at a Distance









تواصل معنا | Contact Us _

+966 545278448 &

alshmmla.light@gmail.com ⊠

@full.light.ksa @